Attorney Docket No. 0465-0884P Amendment filed June 29, 2004

Page 2 of 13

Art Unit: 2871

Application No.: 10/029,146

Amendments to the Claims

1. (Currently Amended) An LCD device having an input line part comprising:

a first line layer formed on a substrate;

a first insulating layer formed on the substrate, having a contact hole therein located at the first line layer;

a second line layer formed on the first insulating layer;

a second insulating layer formed on the substrate, having respective contact holes therein located at the first and second line layers;

a third line layer formed on the second insulating layer;

a passivation layer formed on the substrate, having respective contact holes therein located at the first, second and third line layers; and

a pixel electrode on the passivation layer to electrically connect the first, second and third line layers through each contact hole, said first, second and third line layers providing signals to driver ICs, said driver ICs applying output signals to gate lines or data lines.

- 2. (Original) The LCD device as claimed in claim 1, wherein the first line layer is formed of the same material as a gate line.
 - 3. (Original) The LCD device as claimed in claim 1, wherein the first

Application No.: 10/029,146 Attorney Docket No. 0465-0884P Art Unit: 2871 Amendment filed June 29, 2004

Page 3 of 13

line layer is formed as a double-layered structure inclusive of an AlNd alloy and Mo.

- 4. (Original) The LCD device as claimed in claim 1, wherein the second line layer is formed of the same material as a data line.
- 5. (Original) The LCD device as claimed in claim 1, wherein the second line layer is formed of Cr.
- 6. (Original) The LCD device as claimed in claim 1, wherein the third line layer is formed of the same material as a reflective layer.
- 7. (Original) The LCD device as claimed in claim 1, wherein the third line layer is formed of an AlNd alloy.
- 8. (Original) The LCD device as claimed in claim 1, wherein the LCD device is a reflective LCD device.
- 9. (Original) The LCD device as claimed in claim 1, wherein the LCD device is a transflective LCD device.

Attorney Docket No. 0465-0884P

Amendment filed June 29, 2004

Page 4 of 13

10. (Original) The LCD device as claimed in claim 1, wherein the first insulating layer is formed on an entire surface of the substrate.

11. (Original) The LCD device as claimed in claim 1, wherein the

second insulating layer is formed on an entire surface of the substrate.

12. (Original) The LCD device as claimed in claim 1, wherein the

passivation layer is formed on an entire surface of the substrate.

13. (Currently Amended) A method for manufacturing an LCD device

having a cell array region and an input line part comprising the steps of:

simultaneously forming a gate line on a substrate of the cell array

region, simultaneously, and a first line layer on the substrate at the input line

part;

forming a first insulating layer on the substrate;

forming a semiconductor layer on the first insulating layer of the cell

array region;

Application No.: 10/029,146

Art Unit: 2871

simultaneously forming a data line having source and drain electrodes

at both sides of the semiconductor layer of the cell array region;

simultaneously, and a second line layer on the first insulating layer of the

input line part;

Attorney Docket No. 0465-0884P Amendment filed June 29, 2004

nenament filed June 29, 2004

Page 5 of 13

forming a second insulating layer on the substrate;

Application No.: 10/029,146

Art Unit: 2871

simultaneously forming a reflective layer on the second insulating layer of the cell array region, simultaneously, and a third line layer on the second insulating layer of the input line part;

forming a passivation layer on the substrate;

forming respective contact holes to expose the drain electrode of the cell array region, and surfaces of the first, second and third line layers of the input line part; and

forming a pixel electrode on the passivation layer to electrically connect to the drain electrode of the cell array region and to connect the first, second and third line layers through the contact holes in the input line part, said first, second and third line layers providing signals to driver ICs, said driver ICs applying output signals to said gate line or said data line.

- 14. (Original) The method as claimed in claim 13, wherein the LCD device is a reflective LCD device.
- 15. (Original) The method of as claimed in claim 13, wherein the LCD device is a transflective LCD device.
 - 16. (Original) The method as claimed in claim 13, wherein the first

Application No.: 10/029,146 Attorney Docket No. 0465-0884P

Art Unit: 2871 Amendment filed June 29, 2004

Page 6 of 13

insulating layer is formed on an entire surface of the substrate.

17. (Original) The method as claimed in claim 13, wherein the second insulating layer is formed on an entire surface of the substrate.

18. (Original) The method as claimed in claim 13, wherein the passivation layer is formed on an entire surface of the substrate.